

# FLUORESCENT EMERGENCY BACK-UP BATTERIES/BALLASTS

**SAME DAY SHIPPING** – All in stock items ordered by 6pm EST M-F.

00751-0913

**Immediate back-up lighting when normal AC power fails**  
 90 minute operation • Includes a battery charger & inverter circuit

LUMENS	VOLTS	ITEM NO.	NO. LAMPS	DIMENSIONS (L x W x H)
<b>Philips Bodine</b>				
600	120/277	B90	1-2	9.4" x 2.4" x 1.5"
1400	120/277	B50	1-2	13.3" x 2.4" x 1.5"
3000	120/277	B30	1-2	16.3" x 5.5" x 1.7"
<b>Fulham</b>				
750	120/277	FH1-DUAL-750CFL	1-2	9.4" x 2.4" x 1.5"
<b>LBD Standard</b>				
500	120/277	BAL500	1	9.4" x 2.4" x 1.5"
500	120/277	BALT5-500	1	14.3" x 1.3" x 1.3"
700	120/277	BAL700	1-2	9.4" x 2.4" x 1.5"
750	120/277	BAL650C4	1	9.4" x 2.4" x 1.5"
800	120/277	BALT5-800	1	17.8" x 1.3" x 1.3"
1300	120/277	BALT5-1300	1-2	21.5" x 1.2" x 1.2"
1400	120/277	BAL1400	1-2	13.3" x 2.4" x 1.5"



### Lamp Compatibility Chart

		NO. LAMPS									
		FH1	BAL500	BALT5-500	BAL650C4	B90 & BAL700	BALT5-800	BALT5-1300	B50 & BAL1400	B30 & BAL3000	
Linear Fluorescent Lamps	T5 (W)	1-2	18	—	14-28	—	—	14-28	14-28	—	—
	T5HO (W)	1-2	—	—	—	—	—	—	39, 54	—	—
	T8 (W)	1-2	—	17-40	17-32	17-40	40-110	17-40	17-40	40-110	40-215
	T10 (W)	1-2	—	17-40	—	17-40	—	17-40	17-40	—	—
	T12 (W)	1-2	—	17-40	20	17-40	40-110	17-40	17-40	40-110	40-215
Compact Fluorescent Lamps	4-Pin CFL (W)	1-2	42	13-39	—	40-42	40-42	13-26	26-42	40-42	—
	4-Pin Long CFL (W)	1-2	9-32	—	13-26	13-39	13-39	—	13, 18	13-39	13-42
Special Fluorescent Lamps	T9 Circline CFL (W)	1-2	—	20-40	—	20	—	20-40	20-40	—	—
	T8 U-Bend (W)	1-2	—	32, 40	—	32, 40	—	—	32, 40	—	—
	T12 U-Bend (W)	1-2	—	34, 40	—	34, 40	—	—	34, 40	—	—

### LBD Standard



### Cross Reference Chart

LBD Standard	Philips Bodine	Fulham	Iota
BAL500	LP500, LP400, B100	—	I32/I24, I32
BALT5-500	LP500, LP400	FH7	I28
BAL650C4	BDL94CG	FH2-DUAL-650CFL	—
BAL700	B60, BDL600, B90, BDL900	FH4-DUAL-700L	I40/DL, I48/DL
BALT5-800	LP550	FH9	I54
BALT5-1300	LP600, B50LP	FH8	I540
BAL1400	B50, BDL500, B4CFG	FH5-DUAL-1400L	I420EMA/DL, I420R/DL, 232/DL, I80/I320
BAL3000	B30, B33	FH6-DUAL-3000L	I160AC/DL, I160AC, I880, I160/DL, I162